



## Chair Unit

### Details

#### Chair Unit - IE-24

##### Features

- » A Multi Functional Unit For Comfortable Usage By Ophthalmologist Providing Optimum Utilization and Patient's Comfort.
- » Occupies Minimum Space and Provides Refraction /Examination in One Unit.
- » With Hands On Control Panel For Overhaul Lamp, Slit Lamp Auto Referactometer, Ophthalmoscope / Ratinoscope, Chair Elevation & Auxiliary Outlet, This Versatile Unit has effortless lateral movement.
- » The Chair Can Be rotated 180° Around Vertical Axis With An Electrical Input.
- » Can Be Locked at Any Position.
- » The Elegant Smooth and Noiseless Chair Can Receive Up to 180°Through Motioned Movement Converting it into Minor Surgery Table.

##### Specifications

- » Up/Back (Forward) : By DC Motor 24 V
- » HeadSet : Detachable
- » Elevation Stroke : 190mm
- » Seat Height : 560mm x 760mm
- » Inclination Of BackSeat : 100 to175°
- » Rotation : 0 to180°
- » Foot Switch : For Up/Down Of Chair Only
- » Arm Rest : Mould ed Polyurethane
- » Input Tension : 240 V DC
- » Net Weight : 98 Kg.
- » Load Lifting Capacity : 180 Kg.
- » Required : 2450 mm x 1300 mm in Fully Reclined Position 1700 mm x 1300 mm in Erect Position

##### Stand Unit

- » Slide Table Stroke : 345 mm
- » Power Supply : 0, 2.5, 3, 6, & 12V Selections For Table Mounted Equipments
- » Height Adjustment : 560 mm x 760 mm
- » Safety Stopper : Available
- » Height From Floor : 870 mm
- » Tray Movement : 0 to 90° (Rotated)
- » Table Top Size : 400 mm x 810 mm
- » Trial Lens Set Tray Size : 520 mm x 340 mm x 50 mm
- » Base Plate : 770 mm x 730 mm
- » Main Unit Body : 700 mm x 480 mm x 220 mm
- » Light Pole Length : 1800 mm x 22.5 mm Diameter
- » Prescription : 400 mm x 400 mm
- » Fuse : Slow Blow Type
- » Power Source : 220 V AC
- » Net Weight : 152 Kg